



The best choice of cleanroom wipers.

LT Scientific

-Since 1992-



Cleanroom Wiper

LTK2053B

- Features:**
1. Compatibility with ISO Class 1 cleanrooms
 2. RoHS compliant
 3. Compatibility with general solvents
 4. Fast absorbing

Material: Polyester + Nylon

Construction: Special pattern weft

Sealed Edge Type: Ultrasonic

| Item (Unit) | Specification | | Test Standard |
|---|------------------|----------------------|-----------------|
| Basic Weight (g/m ²) | 150±5 | | GB/T 4669-2008 |
| Extrinsic Capacity (ml/m ²) | ≥300 | | |
| Ions (PPM) | Na ⁺ | ≤0.5 | IEST-RP-CC004.3 |
| | K ⁺ | ≤0.5 | |
| | Ca ²⁺ | ≤0.5 | |
| | Cl ⁻ | ≤0.5 | |
| NVR (PPM) | IPA | ≤500 | IEST-RP-CC004.3 |
| | DIW | ≤500 | |
| APC ≥ 0.3um (counts/ft ³) | 9" * 9" | ≤300 | IEST-RP-CC003.3 |
| | 6" * 6" | ≤200 | |
| | 4" * 4" | ≤100 | |
| LPC (counts/m ²) | ≥0.5um | ≤10 ×10 ⁶ | IEST-RP-CC004.3 |
| Size & Packaging Method | | | GB/T 8806-1988 |
| 9" * 9" | 150 ea/bag | 10 bags/case | |
| 6" * 6" | 300 ea/bag | 10 bags/case | |
| 4" * 4" | 600 ea/bag | 10 bags/case | |

Longtek Scientific Co.,Ltd.

No.8, Industry East Rd. 1, Science Park, Hsin-Chu 300, Taiwan

Tel: +886-3-577-3398

Fax: +886-3-567-9323

Official Website: www.longtek.com.tw

